

**MTZ28-3VI****Reciprocating compressor, MTZ28JE3AVE**

Refrigerants: R404A; R407C; R452A; R407A; R134a; R454C; R407F; R513A; R448A; R455A; R454A; R449A, Segment usage: Refrigeration MT, Compressor power supply [V]: 200-230/3/60, Packing format: Single pack

PRODUCT DETAILS

Gross weight	24.88 Kg
Net weight	23 Kg
Volume	37.73 Liter
EAN	5702428888226
Approval	CE UL UKCA
Brand technique	Reciprocating compressor
Capacity control	Fixed speed
China RoHS compliance	Out of scope
Colour	Blue
Compressor power supply [V]	200-230/3/60
Configuration code	Single
Connection type	Rotolock
Cylinder	1
Description	MTZ028-3
Diameter [mm]	224 mm
Discharge connection height [mm]	68 mm
Discharge connection pipe size [in]	3/8 in
Discharge connection size [in]	1 in
Drawing number	8501024e
Economizer	No
EU RoHS compliance	Yes with exemptions
EU RoHS exemption clause	6(a), 6(a)-I, 7(a), 7(c)-I, 8(b), 9(b)
Factory HP [bar]	25 bar
Factory LP [bar]	25 bar
Family	MTZ
Fitting remark	(shipped with rotolock version only)
Fitting sleeve	ODF
Fitting standard	Rotolock
Frequency [Hz]	60
Gauge port HP	None
Gauge port LP	Schrader
Glass mounting	Threaded
Glass torque [Nm]	50 N-m
GP LP torque [Nm]	15 N-m
High Side TS Max	150 °C
High Side TS Min	-35 °C

Product Detail | Reciprocating compressor, MTZ28JE3AVE

PRODUCT DETAILS

High Side Volume	0.3 L
High value of nominal voltage at 60Hz [V]	230 V
High value of voltage range at 60Hz [V]	253 V
In scope of WEEE and contain batteries	No
IP protection class	IP55 (with cable gland)
Low Side TS Max	50 °C
Low Side TS Min	-35 °C
Low Side Volume	7.5 L
Low value of nominal voltage at 60Hz [V]	200 V
Low value of voltage range at 60Hz [V]	180 V
LRA	57 A
Max pressure (PS) - high side	29.4 bar
Max pressure (PS) - low side	22.6 bar
MCC	16 A
Model number	MTZ28JE3AVE
Motor protection	Internal overload protector
Mounting torque [Nm]	15 N-m
Network power supply [V/Ph/Hz]	208-230/3/60
Number of starts per hour [Max]	12
Oil charge [L]	0.95 L
Oil equalization	3/8" flare SAE
Oil equalization torque [Nm]	30 N-m
Oil reference	175PZ
Packaging height [mm]	385 mm
Packaging length [mm]	330 mm
Packaging weight [Kg]	26 kg
Packaging width [mm]	295 mm
Packing format	Single pack
Packing quantity	1
Phase	3
Power connections	Spade
Product group	Hermetic compressors
Product Name Description	MTZ
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
Refrigerant charge [kg] [Max]	2.5 kg
Refrigerants	R134a R404A R407A R407C R407F R448A R449A R452A R513A R454C R455A R454A
Rotational speed at 60Hz [rpm]	3500 rpm

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ28JE3AVE
PRODUCT DETAILS

SCIP dossier no.	5a332c1b-1d1b-4998-8115-d0929877ecb4
Segment usage	Refrigeration MT
Shipped fittings	Suction and discharge solder sleeves, rotolock nuts, and gaskets
Shipped instructions	Installation instructions
Shipped mounting	Mounting kit with grommets, bolts, nuts, sleeves and washers
Shipped oil	Initial oil charge
Suction connection height [mm]	263 mm
Suction connection material	-
Suction connection pipe size [in]	1/2 in
Suction connection size [in]	1 in
Swept volume [cm³]	48.06 cm ³
Technology	Reciprocating
Test Dif [bar] [Max]	30 bar
Test HP [bar] [Max]	30 bar
Test LP [bar] [Max]	25 bar
Torque earth [Nm]	3 N-m
Torque power [Nm]	3 N-m
Total height [mm]	333 mm
Type	MTZ028
UK RoHS compliance	Out of scope
Winding resistance for three-phase compressors with identical windings [Ohm]	1.41 Ohm
Proposition 65	WARNING: Cancer and Reproductive Harm www.p65warnings.ca.gov

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Accessories

120Z0760 [↗](#)
Mounting, Compressor kit

Mounting kit 1 cylinder low


8156134 [↗](#)
Electrical component, Terminal box

Service kit for terminal box 80 x 96 mm, including 1 cover, 1 clamp


8153010 [↗](#)
Connector, Solder Sleeve

Solder sleeve, P01 (1" rotolock, 3/8" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store [↗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Product Detail | Reciprocating compressor, MTZ28JE3AVE**Accessories****8156130** [🔗](#)**Connector, GASKET**

Gasket, 1"

**8153007** [🔗](#)**Connector, Solder Sleeve**

Solder sleeve, P06 (1" rotolock, 1/2" ODF)

**120Z0575** [🔗](#)**Acoustic hood, Reciprocating**

Acoustic hood for one-cylinder compressor

**7750009** [🔗](#)**Electrical component, Discharge thermostat kit**

Discharge thermostat kit

**8156009** [🔗](#)**Connector, GASKET**

Gasket set, 1", 1-1/4", 1-3/4", OSG gaskets black and white

Spare Parts**7703004** [🔗](#)**Connector, Valve set**

Valve set, V06 (1"~1/2"), V01 (1"~3/8")

**120Z0459** [🔗](#)**Crankcase heater, PTC heater**

PTC heater 27W, CE mark, UL

**8156019** [🔗](#)**Connector, Sight glass**

Oil sight glass with gaskets (black and white)

**8156145** [🔗](#)**Connector, GASKET**

Gasket for oil sight glass (black chloroprene)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.

Spare Parts

**7773106** [🔗](#)**Crankcase heater, Belt heater**Belt type crankcase heater, 54 W, 230 V, CE mark, UL

**8168031** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V06 (1" rotolock, 1/2" ODF)

**120Z0638** [🔗](#)**Lubricant, 175PZ**POE lubricant, 175PZ, 1-litre can

**8168027** [🔗](#)**Connector, Rotolock service valve**Rotolock valve, V01 (1" rotolock, 3/8" ODF)

For more information, please use this link to visit the product page on Danfoss Product Store [🔗](#)

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.